

FFB

FEATURE | FUNCTION | BENEFIT

FEATHERLITE
TRAILERS®

GOOSENECK STOCK TRAILER | MODEL 8117



Find out what real value is with Featherlite's gooseneck livestock trailer Model 8117! It combines the solid quality of Featherlite's all-aluminum construction with an economical price point. Simple and convenient, it features an easy-to-tow width of 6'7". Aluminum floor and running boards are standard on the Model 8117.

PRODUCT SPECIFICATIONS

Trailer width of 6'7"

Lengths of 16', 20' or 24'

6'6" inside height (with option of 7')

Full swing center gate with Featherlite's heavy-duty and easy-to-use slam latch (additional gates available)

Full swing rear stock gate with lockable slider and extra large center post (other options available)

16 LED clearance lights & two oval LED stop/turn lights

Tandem axles (4800# on 16'; 6000# on 20'; 7000# on 24'); Up to 7000# axles are optional

TRAILER HIGHLIGHTS

- Durable all-aluminum construction
- Skid resistant extruded aluminum floor
- Premium Goodyear® tires standard
- E-Z Lube axles standard
- Self-adjusting brakes
- One-piece wiring harness
- Dome light with switch under gooseneck
- Running boards standard
- Removable drop gate panel standard
- Many options available with the PerfectFit™ System
- 10 year limited structural warranty*

OPTIONS

- Aluminum wheels
- Center gate options
- Colored exterior sheets
- Graphics
- Plexiglass
- LED load lights

FFB

FEATURE | FUNCTION | BENEFIT



GOOSENECK STOCK TRAILER | MODEL 8117

FEATURE	FUNCTION	BENEFIT
Aluminum Construction	Featherlites are made with an all-aluminum frame and skin.	With just routine maintenance, aluminum construction has higher resistance to rust and corrosion and in the long run, they hold their value longer. It's also lighter weight, increasing your payload capacity and making for a smoother tow. Featherlite's stock trailers are built with sidewall extrusions that are thicker, allow for stronger welds and vertical tie ring integration and are more scratch resistant.
Uni-Body Design	All components of the Featherlite trailer from side posts to roof rails to roof bows to cross members are engineered into a uni-body design.	The uni-body design makes the trailer stronger and more durable for the long haul.
Crossmembers	3" aluminum crossmembers run every 12" under the trailer.	Featherlites have a solid support system underneath the trailer for your heavy loads of livestock.
Aluminum Floor	Featherlite's skid resistant interlocking extruded aluminum floor is standard.	The aluminum floor is stronger & more durable to last longer through heavy use when hauling livestock.
Center Gate	Full swing center gate with slam latch is standard. Depending on floorplan, choose from 1, 2 or no gates depending on sorting needs.	Aluminum slam latch on center gates allows gates to be shut quickly & easily for convenience and safety when you're loading livestock. Featherlite's slam latch design is even stronger and easier to use for you and your livestock's safety.
Aluminum Running Boards	The running boards on Featherlite livestock trailers are a full-length, one-piece design.	The running boards have a consistently wide platform over the length of the trailer. They are durable and hold up to repeated use in the toughest conditions.

FOR FULL ARRAY OF FLOORPLANS, VISIT WWW.FTHR.COM.

*10-year limited structural warranty on frame and superstructure. Some exclusions apply. Ask dealer for details. **Trailer may be shown with options.