

23,000 LB GOOSENECK FLATBED TRAILER

Standard Sizes:	X	Price \$
GNFB 16' 23K STRAIGHT DECK		
GNFB 18' 23K STRAIGHT DECK		
GNFB 20' 23K STRAIGHT DECK		
GNFB 24' 23K STRAIGHT DECK		
GNFB 26' 23K STRAIGHT DECK		
GNFB 28' 23K STRAIGHT DECK		
GNFB 30' 23K STRAIGHT DECK		
GNFB 32' 23K STRAIGHT DECK		
GNFB 34' 23K STRAIGHT DECK		
GNFB 21' 23K BEAVERTAIL WITH POP-UP AND FOLD OVER RAMPS*		
GNFB 25' 23K BEAVERTAIL WITH POP-UP AND FOLD OVER RAMPS*		
GNFB 26' 23K BEAVERTAIL WITH POP-UP AND FOLD OVER RAMPS*		
GNFB 28' 23K BEAVERTAIL WITH POP-UP AND FOLD OVER RAMPS*		
GNFB 30' 23K BEAVERTAIL WITH POP-UP AND FOLD OVER RAMPS*		
GNFB 32' 23K BEAVERTAIL WITH POP-UP AND FOLD OVER RAMPS*		
GNFB 34' 23K BEAVERTAIL WITH POP-UP AND FOLD OVER RAMPS*		

*Beavertail is 5' of the Overall Length. Ex. GNFB 24' 20K is 19' Straight Deck + 5' Beavertail

Standard Features:

101-1/2" Wide

2 - 10,000 lb, Slipper Spring, Oil Bath, Brake Axles

8 - ST235/80R16-E Tires with Powder Coated Dually Wheels

2-5/16", 30,000 lb, Adjustable Height, Gooseneck Coupler

1 - 12,000 lb, Spring Loaded Drop Leg, Jack (standard on straight deck models)

2 - 12,000 lb, Spring Loaded Drop Leg, Jacks (standard on beavertail models)

Tool Box (standard on beavertail models) and Expanded Metal Tray in Neck

19 lb's Per Foot, 10" I-Beam, Chassis Frame

5" Channel Deck Frame and 3" Channel Deck Crossmembers

Stake Pockets and Pipe Chain Spools with Rubrail Down Both Sides of the Deck

28' and Longer have Chassis to Deck Supports and Chassis Bridging Standard

Polycarbonate Lens Rubber Mounted LED Lights

Spare Tire Mount, Deck Step and Handle

Kiln Dried Douglas Fir Floor

Available Options:	X	Price \$
Spare Tire		
7' Slide in Ramp Package for Straight Deck Models		
Underbody Box with Locking Handle (24", 36" or 48")		
Chassis to Deck Supports (standard on 28' and longer)		
Chassis Bridging (Standard on 28' and longer)		
Deck on Neck		
Weld On Strap Winch \$ _____ ea. x _____ qty. =		
Bolt On Strap Winch \$ _____ ea. x _____ qty. =		
16" Deck Centers		
Full Rear Split Ramp (No Pop Up)		
Extra length, Per Foot \$ _____ x _____ Feet = (38' and Longer Use 22 lb's Per Foot, 10" I-Beam Chassis Frame)		
2nd - 12,000 lb Jack on Straight Deck and Lockable Tool Box		

2 Speed Jack Package		
Electric Activated Hydraulic Brakes		

Price with Options \$

*Due to production improvements, standard and optional equipment are subject to change without prior notice.
All weights and measurements are approximate. Revision 6/2023*